


THE POWER OF CLEAN EFFICIENT LIGHT



DESCRIPTION

An attractive center diffuser 2x2/2x4 direct/indirect linear LED fixture. The DID-M utilizes a white opal acrylic diffuser to provide a higher lumen, soft, balanced illumination for a contemporary appearance and comfortable, low glare light.

The housing and lamp compartment are fully recessed above the ceiling plane, minimizing lamp exposure. The perforated baffle and curved reflector produce a combination of direct and indirect light, fully illuminating the fixture housing.

LAMPS AND DRIVER

Color Temp:	3000k
	4000k
	5000K
	6000k
CRI:	82
Efficacy	120 lms/watt
Driver THD	10.25%
Warranty	5 years

LISTING

All DID Models are certified CSA-CUS, UL and DLC for installations in the U.S. or Canada. The externally driven lamps are CSA approved Master Contract #245571, UL certified, RoHS and LEED compliant.

LED

Recessed Deep Direct/Indirect

DID-22-M-1 (1-lamp)

DID-22-M-2 (2-lamp)

DID-22-M-3 (3-lamp)

DID-24-M-1 (1-lamp)

DID-24-M-2 (2-lamp)

DID-24-M-3 (3-lamp)

FEATURES & BENEFITS

- Center diffuser can be switched out to improve efficiency.
- Built in earthquake feature for added security.
- Latch free diffuser for easier mounting; no moving parts for improved reliability.
- Reflectors and ends feature specially formulated proprietary matte white paint to enhance efficiency.
- Housing Die-formed heavy gauge cold rolled steel.
- Air handling feature available on both 2x2 and 2x4 models
- Basket Options: Extruded white frosted acrylic diffuser or white basket diffuser in lay (Models DID -22/24-HT)
- Finish is low gloss high reflective white finish
- Mounting is standard troffer mounting for T-bar ceilings with earthquake feature
- Lamps: 1,2 or 3-lamp T8 LED

FIXTURE DIMENSIONS:



End View: Recessed Deep Direct/Indirect

All dimensions are inches.

Specifications subject to change without notice.